

## Tilspænding + ventilspillerum udgåede Kubota motorer

Motortype		Topbolt	Plejbolt	Ventilspil
	Z500, Z600, ZH600 D650, D750, D850 V1100, V1200	Z500-B:39,2-44,1 Nm Øvrige: 64,7+69,6 Nm	M7x0,75 26,5-30,4 Nm	Ind + Ud (kold) 0,145-0,185 mm

Motortype		Topbolt	Plejbolt	Ventilspil
02-serien	D1102 > s/n 25273 D1302 > s/n 22541 D1402 > s/n 15906 V1502 > s/n 7433 V1702 > s/n 1247 V1902 > s/n 2322	Bolt + skive  78,5-83,4 Nm	u/flange; 36,3-41,2 Nm  m/flange; 44,1-49,0 Nm	Ind + Ud (kold)  0,18-0,22 mm
	D1102 s/n 25274 > D1302 s/n 22542 > D1402 s/n 15907 > V1502 s/n 7434 > V1702 s/n 1248 > V1902 s/n 2323 >	Flangebolt  93,2-98,1 Nm		

Motortype		Topbolt	Plejbolt	Ventilspil
03-serien	D1403, D1703, V1903 V2203, F2803	93,1-98,0 Nm	u/flange: 36,3-41,2 Nm m/flage: 44,1-49,0 Nm	Ind + Ud (kold) 0,145-0,185 mm